

VISTA-15P

With solid features, robust system capacities and unique and innovative end-user features, the VISTA-15P is the ideal choice for a wide range of applications. The on-board "Load Shed" feature will help reduce costly service calls to replace system batteries that were damaged during extended A.C. power outages. Installers will appreciate the added flexibility of having on-board triggers, up to 32 zones expansion, and custom configurable zone types. Your customers will appreciate Exit Delay countdown at the keypads as well as the added flexibility of programmable Macro buttons and User Definable Schedules.



FEATURES:

- Six on-board hardwire zones standard
- Expandable to 32 total zones when used with Hardwired and/or Wireless Expansion Modules
- Hardwire expansion up to 16 zones
Wireless Expansion up to 26 zones
- Eight Output Devices
 - Relays (Model 4204 relay modules, or 4229 expansion module), and/or
 - X-10 Devices (when used with a 4300 transformer)
- Two low current on-board Trigger Outputs
- *Wireless Keys* can be programmed without using zones
- 50 Event Log viewable at system keypads with Time/Date stamp
- 32 System User Codes assignable to either partition
- Two Installer Configurable zone types allows the installer to "create custom zone types" by assigning all zone attributes
- Multiple Actions on Output Devices depending on system "state"
 - Turn a light Off when system Arms
 - Turn the same light On when system disarms
 - Flash same light when system is in alarm
- Built-in phone line cut monitor with programmable delay and annunciation options
 - Display on system keypads and/or
 - Trigger local sounders and/or
 - Trigger system Bell
- Supports 4 wire, and up to sixteen, 2-wire smokes
 - Works with Sentrol "Clean Me" maintenance signal

Valuable End-User Features

- Now viewable on system keypads:
 - Exit countdown
 - Time & Date Display*
 - Event Log*
- Auto Keypad Backlighting on Entry
- Key switch Arming
- Programmable Macro Buttons & single button arming
- A variety of wireless remote controls for single button operation
- User Scheduling
 - Automatically activates X-10 & Relays at a programmed time
 - Latchkey reports to pagers
 - Auto Arm/Disarm
 - "User Access" Time Windows
- Supports up to Two End User numeric pagers
- VIP module allows system control from any touch tone phone
- Chime by zone

Security Dealer Features

- Automatic System Load Shed
 - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure
- Dynamic Signaling
 - Reduces redundant reporting to the Central Station when multiple reporting methods are used; i.e. Digital Dialer & Alarmnet Radio
- False Alarm Prevention Features to help reduce end users triggering false alarms

**Requires custom alpha keypad*

**Control
Panel**

**ADEMCO
GROUP**

VISTA-15P

SPECIFICATIONS:

Electrical

- Aux power 12 VDC, 600mA max
- Seven hour standby at 400 mA aux load with 4 amp hour battery
- 16.5 VAC/25 VA transformer
- Alarm output 12 VDC, 2.0 amps max
- For UL installations, combined aux and alarm output cannot exceed 700mA

Output Control

- Supports a max of 8 output devices (Combination of relays and/or X-10) PLUS 2 onboard Triggers

Zones

- Six hardwired zones
- Selectable response: 10msec, 350msec, 750msec
- 16 selectable zone types plus 2 configurable zone types
- Programmable swinger suppression

Expansion Devices

- 4219 - eight hardwired zones - 16mA
- 4204 - up to four relays - 15mA standby (each active relay draws an additional 40mA)
- 4229 - eight hardwired zones and two relays - 36mA

Accessories

- Voice module 4286 VIP - 220mA
- 5881ENL up to 8 zones - 60mA, 5881ENM up to 16 zones - 50mA, 5881ENH up to 26 zones - 50mA
- Supports Eagle 1225 & 1221 boards

Keypads

- 6160 custom English (required for programming) - 100mA
- 6150 fixed English LCD 85mA/40mA

Agency Listings

- UL Residential Fire and Burglary and CFM

Smoke Detectors

- Supports up to 16 2 wire smoke detectors
- Supports 4-wire smoke detectors

Communications

- Touch tone or pulse
- Formats supported
 - ADEMCO contact ID
 - ADEMCO 4 + 2 Express
 - ADEMCO low speed
 - Sescoa/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
 - Split
 - Dual
 - Split/Dual - True dial tone detection
- Low battery reports 11.2 - 11.6 VDC
- AC loss and restoral reporting supported

**Control
Panel**

ORDERING:

Part No.	Description
Vista-15P	Control Panel